

500m

Part no.	Piece
15531S	1

1000m

Part no.	Piece
15833S	1

Dederon wire original „Steuer“

- Plastic core 1.4 mm diameter.
- Entwined with 2 special conductors.
- Galvanized metal wire.



GALVADUR 2.5, 625m (=25kg), ø 2.5mm

Part no.	Piece
15945	1

GALVADUR 1.6, 315m (=5kg), ø 1.6mm

Part no.	Piece
15904	1

High tensile wire GALVADUR

- Special wire with a thick galvanized zinc/alu long time protection (95% zinc and 5% aluminium).
- High tensile wire has four times longer life compared to normal steel wires.



250m

Part no.	Piece
15036	1

Steel wire

- Galvanized.
- 1.8mm ø.



200m

Part no.	Piece
15009	1

Spool with 200m

Part no.	Piece
14134	1

Stranded steel wire

- Galvanized.
- 1.5mm ø.



	Spool:	Conductors:	Diametre stainless steel:	Diametre tinned copper:	Resistance:		Max rec. fence length main fences / 12V*:	dry battey fences*:	
15531	500m	2	0.5mm	-	0.35Ω/m	~30kg	13km	4km	1
15833	1000m	2	0.5mm	-	0.35Ω/m	~30kg	13km	4km	1
15945	625m	1	2.5mm	-	0.04Ω/m	~200kg	30km	7km	1
15904	315m	1	1.6mm	-	0.04Ω/m	~500kg	30km	7km	1
15036	250m	1	1.8mm	-	0.05Ω/m	~500kg	25km	6.5km	5
15009	200m	7	0.5mm	-	0.12Ω/m	~200kg	18km	5km	1
14134	200m	7	0.5mm	-	0.12Ω/m	~200kg	18km	5km	1

* Rec. fence length to be reduced to 50% with medium vegetation growth and to 20% with heavy vegetation growth. Icon description please see page 6 and 8.