

Guide Curb, separator LN60

- original Klemmfix interlocking system
- two-tier shape
- skid resistant grips
- composed of dense recycled plastic
- all weather durability
- water drainage
- ease of installation (no anchors, no glue)
- A 90°-curve to be laid out on ~ 11x11m
- snap-in reflective arches (optional) for best nighttime visibility
- weight approx. 19 kg

Part No.	Description	PQ
25581	Guide Curb, yellow, Dimensions: (LxHxW) 1000 x 90 x 270 mm	50
25581weiss	Guide Curb, white, Dimensions: (LxHxW) 1000 x 90 x 270 mm	50

Certified by the BAST acc.to TL-Leitelemente Cert. No.: 94 5 S 001/LU

Curb End piece A, LN61 and End piece B LN62

Part No.	Description	PQ
25582	End piece A, yellow, Moulded-in steel hook, skid resistant grips , Dimensions: (LxHxW) 440 x 90 x 270 mm	1
25582weiss	End piece A, white, Moulded-in steel hook, skid resistant grips , Dimensions: (LxHxW) 440 x 90 x 270 mm	1
25583	End piece B, yellow, Moulded-in receptacle for steel hook, skid resistant grips , Dimensions: (LxHxW) 480 x 90 x 270 mm	1
25583weiss	End piece B, white, Moulded-in receptacle for steel hook, skid resistant grips , Dimensions: (LxHxW) 480 x 90 x 270 mm	1

Certified by the BAST acc.to TL-Leitelemente Cert. No.: 94 5 S 001/LU

Reflective arch, L65

- 14 cat's eyes reflectors
- bow-shaped
- snap-in installation
- clearly shows the raised nature of the curb in the dark
- low profile allows errant tires to flow smoothly over
- Application of reflective arches is optional. It is strongly recommended on motorways and in work zones, especially in the dark.

Part No.	Description	PQ
25584	Reflective arch, yellow, Dimensions: (LxHxW) 180 x 60 x 56 mm	50
25584weiss	Reflective arch, white, Dimensions: (LxHxW) 180 x 60 x 56 mm	50

Certified by the BAST acc. to TL-Leitelemente Cert. No.: 3194

